

View Online at <https://aerobasegroup.com/nsn/4720-01-236-3406>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.625 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

1st layer braided fiber and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant and mildew resistant and oil resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

33.000 inches excluding end fittings

Special Features:

U/o peacekeeper imu; c/o marker 115995-006, insul slvg m23053/5-110-0, adapter 116271-001, fitting cv0096-060, adapter 4741-6b, hose 2575-6

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0