Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-237-4357

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.250 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response                                   |
| Outside Diameter:   |
| 0.578 inches  |
| Minimum Inside Bending Radius:  |
| 3.380 inches  |
| Exterior Color:   |
| Black   |
| Quick Disconnect Size:  |
| 1.480 inches 2nd end  |
| Connection Style:   |
| Plain 1st end   |
| End Connection Design:  |
| Straight 2nd end  |
| Connection Type:  |
| Threaded external pipe 1st end  |
| Burst Test Pressure:  |
| 5000.0 pounds per square inch   |
| Layer Composition And Location:   |
| 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.125 inches 1st end  |
| Hydrostatic Test Pressure:  |
| 3000.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Mildew resistant and oil resistant  |
| Vacuum In Torr:   |
| 50.8  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 28.500 inches   |
| Special Features:   |
| U/o f15 acft  |
|   |



## Media For Which Designed:

Air single response

## Thread Series Designator:

Anpt 1st end

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A542a0