# NSN 4720-01-238-1603

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-238-1603

Cross S	Sectional	Shape:
---------	-----------	--------

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

## **Inside Diameter:**

0.235 inches

#### **Tempurature Rating:**

-450.0 degrees fahrenheit single response and 1200.0 degrees fahrenheit single response

## **Outside Diameter:**

0.439 inches

Minimum Inside Bending Radius:

6.250 inches

#### Inner Conveying Tube Style:

Annular open-pitch corrugated

## **End Application:**

1005-01-221-9448, pneumatic drive assembly

## **Connection Style:**

Swivel nut flare 2nd end

# End Connection Design:

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

# **Features Provided:**

Nuts drilled for lockwire

## Burst Test Pressure:

9800.0 pounds per square inch

# Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

## Maximum Operating Pressure:

1625.0 pounds per square inch

#### **Thread Size:**

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 2nd end

## Flow Angle:

90.0 degrees 2nd end

# Measuring Method And Length:

36.250 inches

# **Thread Series Designator:**

Unf 2nd end

# NSN 4720-01-238-1603

Metallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

