

View Online at <https://aerobasegroup.com/nsn/4720-01-238-1603>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.235 inches

**Temperature Rating:**

-450.0 degrees fahrenheit single response and 1200.0 degrees fahrenheit single response

**Outside Diameter:**

0.439 inches

**Minimum Inside Bending Radius:**

6.250 inches

**Inner Conveying Tube Style:**

Annular open-pitch corrugated

**End Application:**

1005-01-221-9448, pneumatic drive assembly

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Nuts drilled for lockwire

**Burst Test Pressure:**

9800.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1625.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Measuring Method And Length:**

36.250 inches

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0