Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-238-5989

Inside Diameter: 0.234 inches Tempurature Rating: -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response Outside Diameter: 0.453 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: 	Round	s Sectional Shape: न
0.234 inches Tempurature Rating: -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response Outside Diameter: 0.453 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 3000.1 pounds per square inch Hydrostatic Test Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 3000.1 pounds per square inch Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Tempurature Rating: -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response Outside Diameter: 0.453 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No		
-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response Outside Diameter: 0.453 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 0000.0 pounds per square inch Hydrostatic Test Pressure: 0000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit of Measure: Demilitarization: No		
Outside Diameter: 0.453 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Hydrostatic Test Pressure: 10.375 inches working Shelf Life: N/a Unit Of Measure: - Demilitarization: No		
0.453 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 p		
Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire: Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Sheff Life: N/a Unit Of Measure: Demilitarization: No		
3.000 inches Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Sheff Life: N/a Unit Of Measure: Demilitarization: No		
Connection Style: Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 po		-
Swivel nut, inverted flare 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	Conn	ection Type:
16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: - Demilitarization: No		
Layer Composition And Location: 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	Burst	Test Pressure:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	16000).0 pounds per square inch
Maximum Operating Pressure:3000.0 pounds per square inchHydrostatic Test Pressure:6000.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:10.375 inches workingShelf Life:N/aUnit Of Measure:Demilitarization:No	Layer	Composition And Location:
3000.0 pounds per square inch Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	1st lay	yer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	Maxir	num Operating Pressure:
6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	3000.	0 pounds per square inch
Inside Surface Condition: Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	Hydro	ostatic Test Pressure:
Smooth Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	6000.	0 pounds per square inch
Measuring Method And Length: 10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inside	e Surface Condition:
10.375 inches working Shelf Life: N/a Unit Of Measure: Demilitarization: No	Smoo	th
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Meas	uring Method And Length:
N/a Unit Of Measure: Demilitarization: No		
Unit Of Measure: Demilitarization: No		Life:
 Demilitarization: No		
No	Unit C	Of Measure:
No		
		litarization:
Fiig:		
A542a0		