Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-238-5997

(Cross Sectional Shape:
	Round
	Thread Class:
3	3b 1st end
	Thread Direction:
	Right-hand 1st end
I	nside Diameter:
(0.250 inches
	Гетриrature Rating:
-	65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
(Outside Diameter:
(0.375 inches
I	Minimum Inside Bending Radius:
2	2.000 inches
(Connection Style:
ŝ	Swivel nut flare 2nd end
ł	End Connection Design:
Ş	Straight 1st end
(Connection Type:
-	Threaded internal tube 1st end
ł	Features Provided:
F	Reusable end fittings
E	Burst Test Pressure:
	10000.0 pounds per square inch
I	_ayer Composition And Location:
(Duter layer braided corrosion resistant steel wire
I	Maximum Operating Pressure:
	1500.0 pounds per square inch
٦	Thread Size:
(0.500 inches 2nd end
Ş	Seat Angle:
3	37.0 degrees 2nd end
ł	Hydrostatic Test Pressure:
3	3000.0 pounds per square inch
ł	Flow Angle:
2	45.0 degrees 2nd end
١	/acuum In Torr:
Ę	50.8
I	nside Surface Condition:
Ş	Smooth
I	Measuring Method And Length:
	18.125 inches working

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0