## NSN 4720-01-238-6999

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-238-6999

Cross Coational Shanes
Cross Sectional Shape:
Round
Inside Diameter:
1.810 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Bolt Circle Diameter:
3.380 inches 1st end
Flange Thickness:
0.440 inches 1st end
Outside Diameter:
2.220 inches
Minimum Inside Bending Radius:
13.250 inches
Bolt Hole Quantity:
4 1st end
Flange Outside Diameter:
4.500 inches 1st end
Connection Style:
Raised 1st end
Bolt Hole Diameter:
0.560 inches 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
2.740 inches 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 1st end
Connection Type:
Raised face flange 1st end
Burst Test Pressure:
1400.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and 2nd layer braided synthetic cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
350.0 pounds per square inch
Hydrostatic Test Pressure:
700.0 pounds per square inch
Inside Surface Condition:
Smooth

## NSN 4720-01-238-6999

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
17.000 inches
Flange Style:
Round w/ bolt holes 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon and water single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0