## NSN 4720-01-238-9074

**Cross Sectional Shape:** 

Round

Thread Class: 3a 1st end

Thread Direction:
Right-hand 1st end
Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-238-9074

-40.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

End Application:						
F/a-18 hornet aircraft						
Connection Style:						
Swivel nut, inverted flare 2nd end						
End Connection Design:						
Straight 2nd end						
Connection Type:						
Threaded internal tube 1st end						
Thready Qty Per Inch (tpi):						
16 2nd end						
Burst Test Pressure:						
5000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
<b>Maximum Operating Pressure:</b>						
1000.0 pounds per square inch						
Thread Size:						
1.000 inches 2nd end						
Hydrostatic Test Pressure:						
2000.0 pounds per square inch						
Flow Angle:						
90.0 degrees 1st end						
Criticality Code Justification:						
Feat						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
9.010 inches working and 9.670 inches working						
Special Features:						
Weapon system essential						
Media For Which Designed:						
Hydraulic fluid single response						
Thread Series Designator:						
Unjs 1st end						

## NSN 4720-01-238-9074

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0