Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-240-8343

Cross Sectional Shape:
Round
Inside Diameter:
8.0 millimeters
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Flange Thickness:
2.0 millimeters 1st end
Outside Diameter:
Between 0.515 inches and 0.547 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Fluid connection 2nd end
Bolt Hole Diameter:
8.0 millimeters 1st end
Connection Type:
Unthreaded fluid passage bolt 2nd end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Weatherproof and oil resistant and fuel resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0