

View Online at <https://aerobasegroup.com/nsn/4720-01-240-9630>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.310 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Minimum Inside Bending Radius:

1.625 inches

Connection Style:

Swivel nut, compression 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided polyamide cord

Maximum Operating Pressure:

125.0 pounds per square inch

Thread Size:

0.562 inches 2nd end

Hydrostatic Test Pressure:

250.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

558.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

94.000 inches working and 94.750 inches working

Seat Radius:

0.260 inches 2nd end

Special Markings:

Drinking water only, mfr p/n, date of mfr, as standard and operating pressure rating

Supplementary Features:

Public health service publication 308 compliance-fdz apvd matl for aircraft and galley potable water system

Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as1475 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0