## NSN 4720-01-241-8800



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-241-8800 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.810 inches **Minimum Inside Bending Radius:** 7.000 inches Angle Between Rigid Elbow Fittings In Deg: 180.0 **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2500.0 pounds per square inch **Thread Size:** 0.750 inches 2nd end Seat Angle: 37.0 degrees 2nd end

Flow Angle:

90.0 degrees 2nd end

**Outer Covering Environmental Protection:** 

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

27.000 inches

## NSN 4720-01-241-8800

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0