Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-241-9360

Cro	ss Sectional Shape:
Rou	Ind
Thr	ead Class:
3b 1	1st end
Thr	ead Direction:
Rigl	ht-hand 1st end
Insi	de Diameter:
0.37	75 inches
Ten	npurature Rating:
35.0) degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Out	side Diameter:
0.75	50 inches
Min	imum Inside Bending Radius:
4.00	00 inches
Ext	erior Color:
Gre	en
Cor	nnection Style:
Swi	vel nut flare 1st end
Enc	I Connection Design:
Stra	aight 1st end
Enc	I Fitting Component And Material:
Cor	nplete fitting stainless steel all ends
Fitt	ing Component And Surface Treatment:
Cor	nplete fitting passivate 1st end
Cor	nnection Type:
Thre	eaded internal tube 1st end
Thr	eady Qty Per Inch (tpi):
18 1	1st end
Sec	ond End Relationship With First End:
Ider	ntical
Bur	st Test Pressure:
800	.0 pounds per square inch
Firs	at End Swivel Action Capability:
	included
-	er Composition And Location:
	er layer rubber, grade 149fs75, b f goodrich err-100
	kimum Operating Pressure:
	.0 pounds per square inch
	ead Size:
	625 inches 1st end
	at Angle:
37.0) degrees 1st end



Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 47.500 inches working and 48.500 inches working **Thread Series Designator:** Unjf 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0