Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-242-5136

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
1.260 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
14 2nd end
Second End Relationship With First End:
Not identical
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.250 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
11.962 inches working and 12.212 inches working

NSN 4720-01-242-5136

Nonmetallic Hose Assembly - Page 2 of 2



Second End Swivel Action Capability: Not included **Special Features:** Inner conveying tube material-plastic, polytetrafluoroethylene Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unjs 2nd end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0