

View Online at <https://aerobasegroup.com/nsn/4720-01-242-9968>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.985 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

Outside Diameter:

1.188 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel nut, compression 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided polyamide cord

Maximum Operating Pressure:

125.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Hydrostatic Test Pressure:

250.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

558.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

86.375 inches working and 86.875 inches working

Seat Radius:

0.400 inches 2nd end

Special Markings:

Drinking water only, mfr p/n, date of mfr, as standard and operating pressure rating

Supplementary Features:

Public health service publication 308 compliance-fda apvd matl for aircraft and galley potable water system

Thread Series Designator:

Unj 2nd end

Specification Data:

81343-as1475 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0