## NSN 4720-01-243-6291

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-243-6291

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.500 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response				
Outside Diameter:				
0.860 inches				
Minimum Inside Bending Radius:				
7.000 inches				
Exterior Color:				
Black				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 2nd end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Nonskive				
Burst Test Pressure:				
14000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
3500.0 pounds per square inch				
Thread Size:				
0.750 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Outer Covering Environmental Protection:				
Abrasion resistant and oil resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
120.000 inches				
Media For Which Designed:				

## NSN 4720-01-243-6291

Nonmetallic Hose Assembly - Page 2 of 2



-	laa a al	C!	D!	_4
ı	nread	Series	Design	ator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0