

View Online at <https://aerobasegroup.com/nsn/4720-01-244-2440>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

0.550 inches

**Minimum Inside Bending Radius:**

1.000 inches

**Hose Or Tubing Specification/std Data:**

Sae as1227, type 1, or type 2-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel all ends

**Connection Type:**

Threaded internal tube 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

350.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer braided polyamide cord err-100

**Maximum Operating Pressure:**

100.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

200.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Inside Surface Condition:**

Convuluted

**Measuring Method And Length:**

10.375 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-plastic, polytetrafluoroethylene

**Thread Series Designator:**

Unf 2nd end

**Specification Data:**

Sae as1227, type 1, or type 2-81343 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0