

View Online at <https://aerobasegroup.com/nsn/4720-01-244-2441>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

Outside Diameter:

0.550 inches

Minimum Inside Bending Radius:

0.500 inches

Hose Or Tubing Specification/std Data:

Sae as1227, type 1, or type 2-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

350.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided polyamide cord err-100

Maximum Operating Pressure:

100.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

200.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Convuluted

Measuring Method And Length:

14.625 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Thread Series Designator:

Unf 2nd end

Specification Data:

Sae as1227, type 1, or type 2-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0