

View Online at <https://aerobasegroup.com/nsn/4720-01-246-1116>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.985 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

Outside Diameter:

1.310 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Green

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

700.0 pounds per square inch

Layer Composition And Location:

Outer layer braided polyamide cord

Maximum Operating Pressure:

175.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Convuluted

Measuring Method And Length:

48.000 inches working

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 78570 have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0