## NSN 4720-01-246-2675

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-246-2675

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.125 inches
Minimum Inside Bending Radius:
9.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Pausable and fittings
Reusable end fittings
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 12 2nd end
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure:
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 9000.0 pounds per square inch
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location:
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  3000.0 pounds per square inch
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.062 inches 2nd end
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.062 inches 2nd end  Seat Angle:
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.062 inches 2nd end  Seat Angle:  37.0 degrees 2nd end
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.062 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Flow Angle:
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.062 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Flow Angle:  90.0 degrees 2nd end
Thready Qty Per Inch (tpi):  12 2nd end  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.062 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Flow Angle:  90.0 degrees 2nd end  Inside Surface Condition:

Fuel/oil, hydrocarbon single response

Media For Which Designed:

## NSN 4720-01-246-2675

Nonmetallic Hose Assembly - Page 2 of 2



	•	
I hread	Series	Designator:

Un 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0