NSN 4720-01-246-5142

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-246-5142

Cross Sectional Shape:			
Round			
Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.750 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
1.250 inches			
Minimum Inside Bending Radius:			
9.500 inches			
End Application:			
Pettibone corporation truck, forklift model n1-6000rtl			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Reusable end fittings			
Thready Qty Per Inch (tpi):			
12 1st end			
Burst Test Pressure:			
9000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
1.062 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
24.000 inches			
Media For Which Designed:			
Hydraulic fluid single response			

NSN 4720-01-246-5142

Nonmetallic Hose Assembly - Page 2 of 2



ınread	Series	Desig	mator:
Un 1st e	end		

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0