

View Online at <https://aerobasegroup.com/nsn/4720-01-246-6003>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.985 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

Outside Diameter:

1.310 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Green

Angle Between Rigid Elbow Fittings In Deg:

90.0

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

700.0 pounds per square inch

Layer Composition And Location:

Outer layer braided polyamide cord

Maximum Operating Pressure:

175.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Convuluted

Measuring Method And Length:

49.000 inches working

Supplementary Features:

Item has been reviewed for asbestos material. The current approved source, 78570, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0