NSN 4720-01-248-1474

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-248-1474

Cross Sectional Shape:		
Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.188 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response		
Outside Diameter:		
0.343 inches		
Minimum Inside Bending Radius:		
2.000 inches		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Electrostatic discharge capability		
Burst Test Pressure:		
12000.0 pounds per square inch		
Layer Composition And Location:		
Outer layer braided corrosion resistant steel wire		
Maximum Operating Pressure:		
1500.0 pounds per square inch		
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Hydrostatic Test Pressure:		
3000.0 pounds per square inch		
Outer Covering Environmental Protection:		
Alcohol resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant		
Vacuum In Torr:		
50.8		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
18.500 inches working		

NSN 4720-01-248-1474

Nonmetallic Hose Assembly - Page 2 of 2



ınread	Series	Designator
Unjf 1st	end	

Specification Data: 96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0