Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-248-2387

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.500 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.850 inches  |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 8000.0 pounds per square inch   |
| Layer Composition And Location:                                       |
| 1st layer braided fiber and outer layer molded polyurethane           |
| Maximum Operating Pressure:   |
| 2000.0 pounds per square inch   |
| Thread Size:  |
| 0.750 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 22.000 inches working   |
| Thread Series Designator:   |
| Unf 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

## NSN 4720-01-248-2387

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

