

View Online at <https://aerobasegroup.com/nsn/4720-01-249-7945>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.688 inches

Temperature Rating:

-65.0 degrees fahrenheit and 375.0 degrees fahrenheit single response

Outside Diameter:

0.938 inches

Minimum Inside Bending Radius:

4.500 inches

Connection Style:

Swivel nut with compression sleeve 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

3750.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

33.0 degrees 2nd end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant and fire resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.000 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 2nd end

Specification Or Standard:

12 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0