

View Online at <https://aerobasegroup.com/nsn/4720-01-249-7945>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.688 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 375.0 degrees fahrenheit single response

**Outside Diameter:**

0.938 inches

**Minimum Inside Bending Radius:**

4.500 inches

**Connection Style:**

Swivel nut with compression sleeve 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

3750.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

1.062 inches 2nd end

**Seat Angle:**

33.0 degrees 2nd end

**Hydrostatic Test Pressure:**

2000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant and fire resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

24.000 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unj 2nd end

**Specification Or Standard:**

12 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0