Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-249-7945

CI	ross Sectional Shape:
Ro	bund
Th	nread Class:
3b	1st end
Th	nread Direction:
Ri	ght-hand 1st end
In	side Diameter:
0.6	588 inches
Te	empurature Rating:
-6	5.0 degrees fahrenheit and 375.0 degrees fahrenheit single response
Οι	utside Diameter:
).(	938 inches
Mi	inimum Inside Bending Radius:
4.{	500 inches
Cc	onnection Style:
Sv	vivel nut with compression sleeve 2nd end
Er	nd Connection Design:
St	raight 1st end
Cc	onnection Type:
Th	readed internal tube 1st end
Fe	eatures Provided:
Re	eusable end fittings
Th	nready Qty Per Inch (tpi):
12	2nd end
Βι	urst Test Pressure:
37	50.0 pounds per square inch
La	yer Composition And Location:
1s	t layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Ma	aximum Operating Pressure:
10	00.0 pounds per square inch
Th	nread Size:
1.(	062 inches 2nd end
Se	eat Angle:
33	0.0 degrees 2nd end
Hy	/drostatic Test Pressure:
20	00.0 pounds per square inch
Fle	ow Angle:
90	0.0 degrees 2nd end
Οι	uter Covering Environmental Protection:
Сс	prrosion resistant and fire resistant
In	side Surface Condition:
	nooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 24.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unj 2nd end **Specification Or Standard:** 12 size Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0