NSN 4720-01-249-8403

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-249-8403 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.391 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.585 inches **Minimum Inside Bending Radius:** 4.620 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.750 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth

Measuring Method And Length:

16.000 inches

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

NSN 4720-01-249-8403

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0