NSN 4720-01-250-8042

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-250-8042

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.602 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.875 inches
Minimum Inside Bending Radius:
3.880 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and nuts drilled for lockwire and reusable end fittings
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant and oil resistant and ozone resistant

NSN 4720-01-250-8042

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
29.000 inches working
Thread Series Designator:
Unj 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0