Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-251-3106

Cro	ss Sectional Shape:
Rou	nd
Thre	ead Class:
3b 1	st end
Thre	ead Direction:
Righ	nt-hand 1st end
Insi	de Diameter:
0.25	0 inches
Tem	apurature Rating:
-65.0	0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Out	side Diameter:
0.55	0 inches
Mini	imum Inside Bending Radius:
1.00	0 inches
Ang	le Between Rigid Elbow Fittings In Deg:
45.0	
Con	nection Style:
Swiv	vel nut flare 1st end
End	Connection Design:
Elbo	bw 1st end
Con	nection Type:
Thre	eaded internal tube 1st end
Bur	st Test Pressure:
350.	0 pounds per square inch
Lay	er Composition And Location:
Oute	er layer braided polyamide cord
Max	imum Operating Pressure:
100.	0 pounds per square inch
Thre	ead Size:
0.43	8 inches 1st end
Sea	t Angle:
37.0	degrees 1st end
Hyd	rostatic Test Pressure:
200.	0 pounds per square inch
Flov	v Angle:
90.0	degrees 1st end
Insi	de Surface Condition:
Con	voluted
Меа	suring Method And Length:
13.7	'50 inches
Thre	ead Series Designator:
Unf	1st end

NSN 4720-01-251-3106

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

