

NSN 4720-01-251-5268 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-251-5268 **Cross Sectional Shape:** Round

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.610 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.910 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Blue
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Teatures Frovince.
Reusable end fittings
Reusable end fittings
Reusable end fittings Burst Test Pressure:
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location:
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 250.0 pounds per square inch
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 250.0 pounds per square inch Thread Size:
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.875 inches 1st end
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.875 inches 1st end Seat Angle:
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.875 inches 1st end Seat Angle: 37.0 degrees 2nd end
Reusable end fittings Burst Test Pressure: 1000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.875 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure:

26.130 inches

Convoluted

Inside Surface Condition:

Measuring Method And Length:

NSN 4720-01-251-5268

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hread	Series	Designator:	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0