NSN 4720-01-251-7670

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-251-7670

Inside Diameter:					
0.625 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response					
Outside Diameter:					
0.789 inches					
Minimum Inside Bending Radius:					
6.500 inches					
Connection Style:					
Swivel nut, flareless 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Thready Qty Per Inch (tpi):					
12 1st end					
Burst Test Pressure:					
5000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided steel wire					
Maximum Operating Pressure:					
1000.0 pounds per square inch					
Thread Size:					
1.062 inches 1st end					
Seat Angle:					
12.0 degrees 1st end					
Hydrostatic Test Pressure:					
2000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Oil resistant and ozone resistant					
Vacuum In Torr:					
50.8					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
15.500 inches					

NSN 4720-01-251-7670

Nonmetallic Hose Assembly - Page 2 of 2



Ιh	roa	a,	Sariae	I IDEID	ınator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0