NSN 4720-01-251-9340

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-251-9340

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.750 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| End Application: |
| Power lift, truck, forklift; model pdf-20 |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 4000.0 pounds per square inch |
| Thread Size: |
| 0.375 inches 1st end |
| Hydrostatic Test Pressure: |
| 8000.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 27.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Nptf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4720-01-251-9340

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0