NSN 4720-01-251-9346

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-251-9346

Cross Sectional Shape:						
Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.375 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response						
Outside Diameter:						
0.750 inches						
Minimum Inside Bending Radius:						
5.000 inches						
End Application:						
Power lift model pdf-20 forklift truck						
Connection Style:						
Swivel nut flare 1st end						
End Connection Design:						
Straight 2nd end						
Connection Type:						
Threaded internal tube 1st end						
Burst Test Pressure:						
16000.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic						
Maximum Operating Pressure:						
4000.0 pounds per square inch						
Thread Size:						
0.562 inches 1st end						
Seat Angle:						
37.0 degrees 1st end						
Hydrostatic Test Pressure:						
8000.0 pounds per square inch						
Outer Covering Environmental Protection:						
Oil resistant and weatherproof						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
32.000 inches						
Media For Which Designed:						

Fuel/oil, hydrocarbon single response

NSN 4720-01-251-9346

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0