## NSN 4720-01-252-4626

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-252-4626

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.690 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
86.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Unf 1st end

**Thread Series Designator:** 

## NSN 4720-01-252-4626

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0