

View Online at <https://aerobasegroup.com/nsn/4720-01-252-4656>

**Cross Sectional Shape:**

Round

**Wall Thickness:**

Between 0.020 inches and 0.080 inches

**Inside Diameter:**

2.000 inches first end

**Minimum Inside Bending Radius:**

2.000 inches

**Endlength:**

1.250 inches first end

**Connection Style:**

Round first end

**Connection Type:**

Soft first end

**End Inside Diameter:**

2.000 inches first end

**Maximum Operating Pressure:**

4.0 pounds per square inch

**Measuring Method And Length:**

4.000 inches

**Material:**

Steel 2nd ply

**Material Specification:**

Mil-y-1140 military specification single material response reinforcing cord

**Style Designator:**

Fully convoluted w/ wire rings between convolutions

**Test Data Document:**

81205-bms 8-17 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81205-bacd40b manufacturers standard

**Specification Or Standard:**

2 class and 2 type and b grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A229a0

**Mil-std (military Standard):**

Mil-y-1140 spec.