

View Online at <https://aerobasegroup.com/nsn/4720-01-252-4656>

Cross Sectional Shape:

Round

Wall Thickness:

Between 0.020 inches and 0.080 inches

Inside Diameter:

2.000 inches first end

Minimum Inside Bending Radius:

2.000 inches

Endlength:

1.250 inches first end

Connection Style:

Round first end

Connection Type:

Soft first end

End Inside Diameter:

2.000 inches first end

Maximum Operating Pressure:

4.0 pounds per square inch

Measuring Method And Length:

4.000 inches

Material:

Steel 2nd ply

Material Specification:

Mil-y-1140 military specification single material response reinforcing cord

Style Designator:

Fully convoluted w/ wire rings between convolutions

Test Data Document:

81205-bms 8-17 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81205-bacd40b manufacturers standard

Specification Or Standard:

2 class and 2 type and b grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A229a0

Mil-std (military Standard):

Mil-y-1140 spec.