NSN 4720-01-253-4226

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-253-4226

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 1.510 inches |
| Outside Diameter: |
| 2.094 inches |
| Minimum Inside Bending Radius: |
| 7.500 inches |
| Hose Or Tubing Specification/std Data: |
| Ae441-24 fscm 00624 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Connection Style: |
| Swivel nut, flareless 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Socket stainless steel 3rd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Second End Relationship With First End: |
| Identical |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire err-100 |
| Thread Size: |
| 1.875 inches 1st end |
| Seat Angle: |
| 12.0 degrees 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 18.400 inches working |
| Special Features: |
| Inner conveying tube material-plastic, polytetrafluoroethylene |
| Thread Series Designator: |

Unj 1st end

NSN 4720-01-253-4226

Nonmetallic Hose Assembly - Page 2 of 2



| Sı | oec | ific | cati | on | Data: |
|----|-----|------|------|----|-------|
| | | | | | |

Ae441-24 fscm 00624 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0