

View Online at <https://aerobasegroup.com/nsn/4720-01-253-6716>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

1.170 inches

Minimum Inside Bending Radius:

9.500 inches

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nonskive

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

1st layer molded rubber, buna-n and 2nd layer braided wire and 3rd layer molded rubber, synthetic and 4th layer braided wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3200.0 pounds per square inch

Thread Size:

1.0625 inches 1st end

Seat Angle:

12.0 degrees 1st end

Outer Covering Environmental Protection:

Weatherproof and abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

264.000 inches

Special Features:

Media not covered by pac meda are petroleum base and water-oil fire-resistant hydraulic fluids, hot oil and airwater

Media For Which Designed:

Hydraulic fluid and fuel/oil, hydrocarbon and grease and ethylene glycol single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0