NSN 4720-01-253-8601

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-253-8601

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
End Application:
3431-01-090-1231
Connection Style:
Flared 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated cotton fabric and 2nd layer rubber impregnated cotton fabric and outer layer molded rubber, synthetic
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
900.000 inches
Special Features:
Assembly includes 2 brass insert, hose barbed
Media For Which Designed:

Air single response

NSN 4720-01-253-8601

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Sorios	Designator	
ımread	i Series	Designator	

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0