NSN 4720-01-254-0189

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-254-0189

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| |
| Right-hand 1st end Inside Diameter: |
| |
| 0.375 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 257.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.750 inches |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 900.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fabric and 2nd layer spirally laid steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Thread Size: |
| 0.500 inches 1st end |
| Outer Covering Environmental Protection: |
| Ozone resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 140.000 inches working |
| Special Features: |
| 1 cam lock fitting per ms35746 furnished for ea end |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Nptf 1st end |
| Specification Data: |
| 96906-ms39325-9-140-b government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4720-01-254-0189

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0