NSN 4720-01-254-1256

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-254-1256 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.766 inches **Minimum Inside Bending Radius:** 4.625 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided steel wire and outer layer braided textile yarn **Maximum Operating Pressure:** 1850.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth

Measuring Method And Length:

11.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-254-1256

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0