NSN 4720-01-255-1939

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-255-1939

Ten	าทเม	ratur	e R	atin	a:
	ıpu:	atui	C ! \	atili	ъ.

35.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Flange Thickness:

0.115 inches 2nd end and 0.135 inches 2nd end

Minimum Inside Bending Radius:

7.000 inches

Exterior Color:

Green

Center To Center Distance Between Bolt Holes Along Width:

1.485 inches 2nd end and 1.515 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.485 inches 2nd end and 1.515 inches 2nd end

Bolt Hole Quantity:

4 1st end

Flange Length:

1.900 inches 2nd end

Flange Width:

1.900 inches 2nd end

Bolt Hole Diameter:

0.218 inches 2nd end and 0.224 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

800.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch

Hydrostatic Test Pressure:

400.0 pounds per square inch

Measuring Method And Length:

43.500 inches and 44.500 inches

Flange Style:

Rectangular (includes square) 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4720-01-255-1939

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0