## NSN 4720-01-255-1939

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-255-1939

Tempurature Rating:
35.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Flange Thickness: 0.115 inches 2nd end and 0.135 inches 2nd end
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Green
Center To Center Distance Between Bolt Holes Along Width:
1.485 inches 2nd end and 1.515 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
1.485 inches 2nd end and 1.515 inches 2nd end
Bolt Hole Quantity:
4 1st end
Flange Length:
1.900 inches 2nd end
Flange Width:
1.900 inches 2nd end
Bolt Hole Diameter:
0.218 inches 2nd end and 0.224 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Plain face flange 2nd end
Burst Test Pressure:
800.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch
Hydrostatic Test Pressure:
400.0 pounds per square inch
Measuring Method And Length:
43.500 inches and 44.500 inches
Flange Style:
Rectangular (includes square) 2nd end
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

## NSN 4720-01-255-1939

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

