## NSN 4720-01-257-0503

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-257-0503 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 165.0 degrees fahrenheit single response **Outside Diameter:** 0.480 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1250.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

19.000 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

## NSN 4720-01-257-0503

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0