NSN 4720-01-258-5083

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-258-5083

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
1.000 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
1.406 inches					
Minimum Inside Bending Radius:					
12.000 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Features Provided:					
Nonskive and reusable end fittings					
Burst Test Pressure:					
4000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided steel wire and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
1000.0 pounds per square inch					
Thread Size:					
1.312 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
2000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Abrasion resistant and oil resistant and water resistant and weatherproof					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
170.000 inches					
Media For Which Designed:					
Fuel/oil, hydrocarbon single response					

NSN 4720-01-258-5083

Nonmetallic Hose Assembly - Page 2 of 2



-	laa a al	C!	D!	_4
ı	nread	Series	Design	ator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0