NSN 4720-01-259-2248

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-259-2248

2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.344 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response			
Outside Diameter:			
0.547 inches			
Minimum Inside Bending Radius:			
2.500 inches			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
End Fitting Component And Material:			
Complete fitting aluminum alloy all ends			
Connection Type:			
Threaded internal tube 1st end			
Second End Relationship With First End:			
Not identical			
Burst Test Pressure:			
6000.0 pounds per square inch			
First End Swivel Action Capability:			
Not included			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1000.0 pounds per square inch			
Thread Size:			
0.562 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
3000.0 pounds per square inch			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
127.500 inches			

NSN 4720-01-259-2248

Nonmetallic Hose Assembly - Page 2 of 2



Speci	ıaı r	·eatu	ıres
l			4.

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0