## NSN 4720-01-260-4390

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-260-4390 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.630 inches **Minimum Inside Bending Radius:** 2.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided synthetic cord and 2nd layer braided synthetic cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.375 inches 1st end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Outer Covering Environmental Protection:** Abrasion resistant **Inside Surface Condition:** 

**Measuring Method And Length:** 

12.000 inches working

Smooth

## NSN 4720-01-260-4390

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator	:
--------------------------	---

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0