

View Online at <https://aerobasegroup.com/nsn/4720-01-260-7314>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.750 inches and 0.797 inches

Temperature Rating:

-40.0 degrees celsius and 93.0 degrees celsius single response

Outside Diameter:

Between 1.406 inches and 1.469 inches

Minimum Inside Bending Radius:

11.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

20000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and cold resistant and oil resistant and ozone resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

8.000 inches working

Special Features:

End fitting matl comp 12l14 steel astm a108 or sae j403 uns g12144

Media For Which Designed:

Fuel/oil, hydrocarbon and gas and hydraulic fluid and hydraulic fluid, water base and oil, lubricating, diester base and water single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0