## NSN 4720-01-260-9465

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-260-9465

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.329 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.547 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
7.875 inches working and 8.125 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon and oil, lubricating, diester base single response

Unjf 1st end

**Thread Series Designator:** 

## NSN 4720-01-260-9465

Nonmetallic Hose Assembly - Page 2 of 2



81349-mil-h-83796/1 government specification

**Specification Or Standard:** 

6 size

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0