NSN 4720-01-261-1037

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-261-1037

Craca Sectional Shape
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
1.750 inches
Exterior Color:
Black
Connection Style:
Swivel, plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 2nd end
Features Provided:
Reusable end fittings
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber, synthetic and 2nd layer braided textile yarn and 3rd layer braided textile yarn and outer layer molded rubber,
synthetic
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Hydrostatic Test Pressure:
450.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
59.000 inches
Special Features:
One and fitting fixed and other and swivel: finish with electrodenosited zinc with supplementary chromate treatment

Air single response

Media For Which Designed:

NSN 4720-01-261-1037

Nonmetallic Hose Assembly - Page 2 of 2



Thre	ead	Series	Design	nator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0